

## PRODUCT DATA SHEET

Part No: AC500604

Date of Issue: 20/08/2019

**ARC Plus** UltraSoft CAT 4 Arc Flash Hood with Lift Front Visor

### Features

- Manufactured from 3 layers of UltraSoft Arc Rated Flame Retardant S301 237gsm Orange fabric
- UltraSoft is 88% cotton, 12% high tenacity nylon
- Sewn with Nomex thread
- Garment is NFPA CAT 4 compliant, 40 cal/cm<sup>2</sup>
- Grey Polycarbonate Highly Transparent 3Phase<sup>®</sup> Lift Front Hood
- Window Size: 54cm x 21cm x 0.23cm
- Lift Front Hood Weight: 499grams
- The Lift Front Visor and Hood are fitted onto a hard hat
- Hard Hat included
- Made In Australia



### Standards Compliance

#### Arc Flash Hood

- NFPA 70E Electrical Safety in the Workplace compliant CAT 4, ATPV 47 cal/cm<sup>2</sup>
- AS/NZS 1020:1995, The Control of undesirable static electricity
- Oeko-Tex Standard 100 Class II
- AS/NZS 1906.4.2010, High Visibility Material for Safety Garments
- EN ISO11612:2015 Protective Clothing Protect Against Heat & Flame A1, A2, B1, C1
- ASTM F1959, Standard Test Method Determining Arc Rating of Materials for Clothing

## Standards Compliance

### Visor

- NFPA 70E compliant CAT 4, ATPV 40 cal/cm<sup>2</sup>
- ANSI Z87.1, Occupational And Educational Personal Eye And Face Protection Devices
- ASTM F2178, Standard Method for Determining the Arc Rating and Standard Specification for Face Protective Products

### Hard Hat

- AS/NZS 1801:1997, Occupational Protective Helmets
- For further Technical Specifications and features please contact MSA Safety.

**Disclaimer:** The information contained in this data sheet is believed to be true at the time of printing. It is up to the user to determine suitability of use, or potential infringement for specific applications.